

Western Speedway

Western Promotions Ltd. 2207 Millstream Road Victoria, B.C. V9B 0J7

Phone at track: 250-474-2151

Derby Rules (Last updated 2013)

Any 1980 or newer uni-body cars allowed, 4 cyl or 6 cyl only such as Tempo's, Mustang's, BMW's, Daytona's, K-Cars, Dodge 500's, Grand Am's, Grand Prix's and so on....

NO FULL FRAME cars allowed and no Camaro's.

All interior must be removed (DASH MUST STAY IN). If you prefer dash out you must install a dash bar minimum 2"x3/16" with flanges on both ends and mounted with adequate bolts, washers and plates across where dash used to be and chain steering column to bar.

All windows, lights, and grill if plastic or fiberglass must be removed.

Windshield bar must be at least 2" in width. If no windshield you must have screen past halfway across opening.

Must pad the steering column.

Can use turn key ignition or toggle switch start.

If electronic fuel pump you must put an "E" on roof sign and must have shut off button (may use original fuel pump with ignition).

Must have driver's door and upright padded. Upright must be bolted with four 3/4" or bigger bolts in roof and floor behind driver's seat. (Does not need kicker to back seat area)

All sunroofs must be covered with tin or equivalent metal with minimum 4 bolts.

Cross bar from driver's door to passenger door with adequate bolts, plates and washers (Doors must be chained or bolted on passenger side if no door bar).

Minimum 8" door bar in width on driver's side, passenger door bar optional(Cannot go inside wheel wells).

Driver's seat must be bolted solid or left in original place (No bench seats).

5-point racing harness with anti sub belt and snell 95 or newer helmet with fire proof racing suit required.

Window net must be bolted on tight (If it falls down you're out NO EXCEPTIONS).

Battery box must be wood or metal with foam inside and lid closed with metal strap or seatbelt and must be bolted solid with four 1/2" bolts or bigger on passenger floor (NO plastic marine boxes allowed).

Gas box must be in back seat bolted solid with four 1/2" bolts or bigger and must have drain hole under box (NO plastic boxes allowed, such as coolers).



Western Speedway

Western Promotions Ltd. 2207 Millstream Road Victoria, B.C. V9B 0J7

Phone at track: 250-474-2151

Original gas tanks MUST be removed.

NO pinning of body mounts allowed.

Must chain bumpers solid enough to not fall off and bumper shocks must be stock and not replaced with square tubing (NO pinning or welding allowed).

Hood may be pinned with a maximum of 1" redi rod or bolts in no more than 4 spots and hood latch must be removed for quick access in case of fire.

MUST have two 4" by 6" holes in hood above exhaust manifolds in case of fire.

Trunk or hatch MUST be chained closed (trunk lid must remain in stock position).

Trunk may be pre-kinked so it will go up instead of down but no cutting or bending of the frame allowed.

Trailer balls and hitches must be removed.

Floor shifter optional but recommended.

Hand throttle cable may be installed.

Locking rear ends may be done.

Roof sign must be at least 2' by 2' but no larger than 3' by 3' and must be white with black numbers (If unable to read you will not be counted).

No black cars allowed.

NO forklift or trailer tires allowed. NO valve stem blockers allowed. Snow tires or truck tires are ok but must NOT be studded (NO EXCEPTIONS as all tires will be checked after the event).

Expansion tanks may be put in place of radiators but must be solidly secured.

NO welding allowed anywhere on any vehicle!!

2 minute time limit from last hit.

2 fire limit

Mini Truck Rules

All previous rules apply with following additions.



Western Speedway

Western Promotions Ltd. 2207 Millstream Road Victoria, B.C. V9B 0J7

Phone at track: 250-474-2151

4 cyl trucks only such as S-10's, Mazda's, Ranger's and so on...

NO 4x4 only 2 wheel drive.

Regular cabs must have full cage, extra cab can run upright with cross bar.

Fuel tank must be inside a box mounted in middle of truck box behind the cab with four 3/4" bolts or bigger.

May bolt truck box in no more than 4 spots with maximum 1" bolts.

May chain or bolt tailgate in a maximum of 4 spots.

Mandatory drive shaft hoop.

May use body mounts in rad support for hood pins, all other mounts must remain stock.

Any questions please call BJ at 250-516-0053